

Instructions for Use

Intra-oral Adjustment/Polishing for Zirconia and Lithium Disilicate

- 1 Suitability for use
 Visually check the polishers for cracks, chips and corrosion.
 Ensure that the polishing medium remains secure on the bur. Do NOT use if damaged or worn out.
- Instruments are shipped non-sterile. Complete cleaning and sterilization instructions may be found at www.garrisondental.com/sterilization. Autoclave the instruments at 134°C with a holding time of five (5) minutes and a drying time of ten (10) minutes. It is the responsibility of the dentist or licensed practitioner to ensure effective sterilization.
- Storage
 Store the polishers in the sterilization container until required for use.
 Storage should be in dry, clean conditions at ambient temperature.





Precautions

- A. The device is to be used by a dentist or licensed practitioner
- B. Wear gloves when handling instruments
- C. Handpieces should be maintained in good working order
- D. Ensure the polisher is securely gripped in the handpiece collet
- E. Wear eye protection to shield against particles
- F. Wear a surgical mask to avoid inhalation of particles

Use

- A. Maintain constant movement to avoid localized heating and potential damage
- B. The speed range for use is 7000-10,000 RPM Do NOT exceed 20,000 RPM
- C. Avoid applying excessive pressure or leverage
- D. Best results are achieved by using polishers in order from coarse to fine grit

Post Use

Used burs should be considered contaminated and require appropriate handling precautions for subsequent reprocessing.

For current instructions including cleaning and sterilization, please visit www.garrisondental.com/sterilization

150 DeWitt Lane

Fax 616.842.2430

Phone 616.842.2244

